

Integrated Control Box JCB35M1



Data sheet

JCB35M1

- JCB35M1, with breakthrough and innovative design, is integrated with handset. The operation of column's lifting can be realized without external handset.
- From an environmental view, the JCB35M1 is a good choice with extremely low power consumption in standby mode: only 0.1W. The Anti-Collision function protects body and objects from being squeezed or collided during the lifting. The light with three colors indicates the working conditions.
- Compatible with JC35QT frame, suitable for both home and office.



Features

- Can be connected to 1 column
- Color: black
- Shell material: fireproof ABS
- Protection against overload
- Protection against overheat
- Protection against short circuit
- Designed with a soft start/stop function
- Certification: CE

Option

- 2.4G wireless receiver box, remote control
- Bluetooth receiver box, controlled by mobile phone
- 3S system accessories, used to improve the sensitivity of Anti-Collision and enhance the safety, stability and self-adjusting performance of the system.

Usages

- Duty cycle: 2/18; 2 minutes continuous use followed by 18 minutes not in use
- Usage environment: indoor
- Ambient temperature: -25°C+70°C

Technical specifications

- input voltage: DC22V-32V
- output voltage: DC18V-33V
- output power: 24V/6A
- Low standby power consumption: 0.1W
- size:108.9×86×28
- weight: 0.1KG

Dimensions

