

JCB36NE2

Control Box



Data sheet

JCB36NE2

- JCB36NE2 control box, as an upgraded version of JCB36N2 control box, has stronger performance and richer functions.
- Support fast charging function of handset with fast charging USB socket.
- Added DC socket for external accessories.
- Equipped with a six-axis sensor, more sensitive to setbacks.
- 0.1W ultra-low standby power consumption.



Features

- Dimensions: 253.3*90*40mm
- Number of control columns: 1-2
- Color: Black
- House: ABS with snap structure, no screws
- Installing way: Screw on the table top or use the slot on the frame to fasten
- Overload protection: Set the limit value to avoid over burden motion
- Overheating protection
- Short circuit protection
- Anti Collision
- Slow start and slow stop, increase the lifting buffer to enhance the operating experience
- Power: 350W
- Control method: No relay
- Handset socket: Ten-core (RJ45 10P10C)

Option

- 2.4G-box, used to control the column lifting by remote control.
- Bluetooth box, used to control column lifting through APP.
- 65W fast charging box for mobile phone, tablet, laptop charging.
- Lithium battery for powering the control box.

Usages

- Duty cycle: S1-10 min. Continuous work for most 2 minutes in a period of 20 minutes
- Ambient surrounding: Indoor

Technical specifications

Model	JCB36NE2	JCB36NE2P
Lithium battery powered	×	√
The DC jack	×	4Pin

Dimensions

