
JS36DE1-3-S

Lifting column



**TECHNOLOGY
DRIVES INTELLIGENT LIFE**

Data sheet

JS36DE1-3-S

- JS36DE1-3-S is an oval shape 3-segment no hole column, perfect for a wide range of different desk applications. The column is very clean and compact in design, and compared with the JS36DE1-2-S, the adjustable range is larger and it can meet different customers. JS36DE1-3-S has the same outer dimensions and mounting holes as JS36DE1-2-S, which makes them compatible and they can be used in the same frame & foot construction.
- JS36DE1-3-S is available in several standard colours to fit into a wide range of desk designs.
- The function of anti-collision minimize the risk of damages when desk collision with an obstacle.
- JS36DE1-3-S is compatible with all the standard Jiechang control boxes, and ensures a very low and pleasant noise level, and steady movement. Furthermore, the system has a very low standby power consumption less than 0.1W.



Features

- With 2mm thickness oval tube and 3mm optimized motor housing design for extra strength and stability
- The tube is no hole design
- Max. load capacity is 800N per column
- Fit with JCB35N series Jiechang control boxes to realize max speed 40mm/s
- Low noise level <50dB
- Max. Bending moment: 150N.m
- Standard installation length: 560mm
- Standard stroke length: 650mm
- Outer tube size: 91x57mm of oval shape
- Motor housing dimension: 190x96x48mm
- Motor: Jiechang design high power motor
- Hall sensor enabling parallel drive
- Surface: Powder coating with standard color: White (RAL9016), Black (RAL9005), Grey (RAL7045)

Option

- Customized colours
- Compatible with several different styles of feet
- PVC-free column
- Bracket for crossbar

Usage


- Single or 2, 3, or 4 parallel drive or even multi-parallel with up to 12 columns, and can fit with Jiecang QT, TS, TT, TF standard frame
- Compatible with Jiecang control box: JCB35N1, JCB35N2, JCB35N3 JCB35N4
- Duty cycle: 10 %, Max. 2 minutes operation/Min. 18minutes rest of continuous use at full load
- Working environment: Indoor
- Storage and transport temperature :-10°C + 70°C

Technical specifications

Type	Rated load (N)	Self locking (N)	Typical current at rated Load (A)	Typical max speed 0 load~ Rated load (mm/s)	Duty cycle	Stroke length (mm)	Built-in length (mm)
JS36DE1-3-S	800	1200	5	35	10%	650	560

Note: The measurements above are made in connection with the control box JCB35N series.

Dimensions



Ordering Key

