


Four elevating column

JS36DS8-4-S



Data sheet

JS36DS8-4-S

- JS36DS8-4-S is a lifting column mit 4 stages, which is suitable for office, home and business environment.
- Compared with standard lifting column, it occupies lower installation length, higher stroke, faster speed.
- The anti-collision function of it minimizes the risk when the desk hits an obstacle.
- It is suitable for products with low load and high installation length requirements, such as desk converter and lifting tea table.



Features

- Square lifting column, 1.5mm pipe thickness and 3mm thickened motor housing, ensuring the strength and stability of the column
- No hole design on the pipe
- Maximum thrust of a single column: 300N
- Matched with JIECANG N type control box, no load & Load ensuring stable speed: 50mm/s
- Low noise level: ≤ 52 dB
- Maximum lateral force: 100N.m
- Standard installation length: 450mm
- Standard stroke: 700mm
- Out pipe size: 70x70mm
- Motor housing size: 190x96x48mm
- Motor: JIECANG self-made high-efficiency motor
- Double Hall feedback
- Surface: powder coating—standard color: white, black, grey


Usages

- Matched control box: JCB35N1/JCB36N1; JCB35N2/JCB36N2; JCB35N3/JCB36N3; JCB35N4/JCB36N4; JCB35NS1; JCB35NS2
- Duty cycle: 10%; work for 2 minutes and take an 18-minute break
- Application environment: Indoor
- Storage and transportation temperature: -10°C~70°C

Technical specifications

| Type | Load (N) | Self-lock (N) | Rated load current (A) | Maximum speed no load ~ rated load (mm/s) | Duty cycle | Stroke length (mm) | Retracted length (mm) |
|-------------|-------------|------------------|------------------------------|---|------------|--------------------------|-----------------------------|
| JS36DS8-4-S | 300 | 1200 | 6 | 50 | 10% | 700 | 450 |

Dimensions



Ordering key

JS36DS8 - 4 - S - 700/450 - 0 - H - 0

